

### 4.5" 10X / 12X 50M IR PTZ



	CB-12X-0502	CB-10X-0502
Horizontal Rotation Speed	0.02° - 200°/s	
Tilt Rotation Speed	100°/s	
Horizontal Rotation Range	360°	
Tilt Rotation Range	90°	
Auto Flip	Horizontal 180°, Vertical 180°	
Auto Control IR LED	PWM	
A-B Scan	User Programmable	
A-B / 360° Scan Speed	0-64 Levels setting available	
Dwell Preset	2-60s Interval available	
Present Point	220	
Go to Preset Speed	01-64 Levels available	
Guard Tours	4 Groups	
Guard Points	Max. 16 Points, Dwell Time user selectable	
Pattern Scan	4pcs	
Pattern Scan Record	Max.15 Minutes, Max. 512 Commands	
Home Pos Time	0-60 Minutes available	
PWR on Action	Memory as Power Off / 360° Scan / A-B Scan / Preset Cruise1-3	
Communication Protocol	Pelco D, Pelco P	
Communication	RS-485	
Baud Rate	1200 / 2400 / 4800 / 9600bps	
Privacy Mask	8-24pcs (According to Zoom Module Type)	

<b>3D Location</b>	Support	
<b>Time Scheduling Function</b>	8 tasks	
<b>Operating Temp.</b>	-40°C ~ +60°C	
<b>Operating Humidity</b>	≤95% Non Condensing	
<b>Heater &amp; Blower</b>	Auto Temperature Control	
<b>Power</b>	AC/DC15-28V ≤ 3A	
<b>Lighting Protection</b>	Transient Voltage 6000V	
<b>IR Illumination Distance</b>	50M	
<b>Power Consumption</b>	≤ 20W	
<b>Compatible Camera</b>	1/3" SAMSUNG SCM-2121P	1/3" SONY Effio-E , Color: 650TVL, B/W: 700TVL, IR-CUT
<b>Led Angle of Illumination</b>	Ø16=6	
<b>Lens</b>	12X, f=3.94 to 46.05mm (F=1.67 to 1.88)	10X, f=5-50mm (F=1.6)
<b>Certification</b>	CE / FCC / RoHS	