


SONY Effio-A 800TVL 2D+3D DNR 20M IR Dome



CP-MD700IR24

Image Sensor	1/3" SONY EXview HAD II CCD (ICX873)
Scanning System	2 : 1 Interlace
Picture Elements	PAL:1028 x 596; NTSC: 1028 x 508
S/N Ratio	More than 52 dB (AGC off)
Resolution	Color: 720 TVL; B/W: 800 TVL
Min. Illumination	Color: 0.01Lux, B/W: 0.001Lux
Illuminate Distance	20M / 24pcs x ϕ 5mm IR Led
Lens	3.6 / 6.0mm Lens
White Balance	ATW / One Push / Manual / Indoor / Outdoor / Auto
DWDR	On / Off (Level adjustable)
DNR	2D+3D DNR
HLC	On / Off
BLC	On / Off
Gain Control	Yes
Motion Detection	On / Off (4 Zone Selectable)
Privacy	On / Off (4 Zone Selectable)
Mirror	On / Off
DEFOG	On / Off
E. Zoom	E-Zoom (Max x2~x255)
Picture Adjustment	Yes
Operation Temp.	-10°C ~ +50°C
Power Supply	DC12V \pm 10% Max 400mA
Dimension	94(D) x 69(H) mm / 400g
Certification	CE / FCC / RoHS