


SONY Effio-V 800TVL WDR 40M ArrayIR Camera



CB-OC750IR

Image Sensor	1/3" SONY Super HAD II (ICX663)
Scanning System	2 : 1 Interlace
Picture Elements	PAL:1028 x 596, NTSC: 1028 x 508
S/N Ratio	More than 52 dB (AGC off)
Resolution	Color: 750 TVL,
Resolution	B/W: 800 TVL
Min. Illumination	Color: 0.01Lux, B/W: 0.001Lux
Illuminate Distance	40M / 1 x 42 MIL Array IR Led
Lens	4.0 / 6.0 / 8.0 / 12.0 / 16.0 / 25.0mm Lens
White Balance	ATW / One Push / Manual / Indoor / Outdoor / Auto
WDR	On / Off (Level adjustable)
DNR	2D+3D DNR
HLC	On / Off
BLC	On / Off
Gain Control	Yes
Motion Detection	On / Off (4 Zone Selectable)
Privacy	On / Off (4 Zone Selectable)
Mirror	On / Off
DEFOG	On / Off
E. Zoom	E-Zoom (Max x2~x255)
Picture Adjustment	Yes
Operation Temp.	-10°C ~ +50°C
Power Supply	DC12V±10% Max 400mA
Dimension	200(L) x 90(W) x 80(H) mm / 800g
Certification	CE / FCC / RoHS